

<u>lincon</u>™



## Parts and Specifications

Copyright © Mincon 2021, All Rights Reserved.



## Mincon MR92 Parts and Specifications

		21	Item	Part Number	Description	Notes		
	1 0				MR92AS01	Hammer 3½" Remet		
2	8	(	22		MR92AS02	Hammer 90mm ARDA		
3	3			1	1300-0700	Internal Circlip		
U .		23	2	BS132	O Ring x 2 (OD)	3½" Remet only		
				3	MX4044AT01	Adaptor Tube	3½" Remet only	
4	000				MR92AT02	Adaptor Tube	90 ARDA only	
5	$\geq$		4		BS 126	O Ring x 2 (Adaptor tube ID)	· ·	
0	-	PHIS		5	BS 036	O Ring (Airscreen)	Not required for ARDA	
	IIII		24	6	MX4044SC01	Airscreen	Not required for ARDA	
7	7			7	MX4044BH01	Backhead	3½" Remet only	
					MX4044BH02	Backhead	90 ARDA only	
	0			8	BS 233	O Ring (Backhead)		
	_			9	8405-137	Check Valve Seal		
8	000			10	MX4044CV01	Check Valve Plunger		
9	0			11	MX4044SP01	Check Valve Spring		
10	0			12	MX4044SM01	Steel Make Up Ring		
na ar				13	MX4044LR01	Lock Ring		
11	8			14	MX4044TT01	Top Tube		
93			25	15	BS 126	O Ring x 2 (Top tube inner)		
12	0			16	MX4044SS01	Spacer		
13	0			17	MX4044ST01	Sample Tube		
				18	BS 128	O Ring (S/T mount ID)		
	- 11			19	MX4044DR01	Sample Tube Mount		
14	- 65			20	BS 138	O Ring (S/T mount OD)		
45	0		00	21	BS 036	O Ring (Seating ring)		
15		0	26	22 23	MX4044SR01	Seating Ring		
16	0				MX4044IC01	Inner Cylinder		
8		27	24 25	MX4044PN01 MR92WS01	Piston Wear Sleeve			
			00	26	MX4044PR01	Piston Retain Ring		
a C		28	27	MR92BB01	Aligner Bearing Bush			
		C ,	29	28	BS 232	O Ring x 2 (Aligner)		
17	17		30	29	MR92BR01	Bit Retaining Rings		
5770			16067	30	BS 139	O Ring x 1 (Bit rings)		
	- 11		31	31	MR92CSxxx	Chuck Sleeve		
	- 11		01	32	MR92CK01	Chuck		
	- 11				MR92OK01	O Ring Kit		
	III.		32		MR92MK01	Make-up Kit		
	10	0				·		
200020		offin						
18	0							
19	8							
	0	403						
20		6000						
		-000						

Specifications	Metric
Hammer Outside Diameter	92mm (3.6")
Hammer Length (Less Bit, Backhead Shoulder to Chuck)	1,146mm (45")
Backhead Spanner Flat Size	76mm (3")
Drill Bit Shank Type	MR92
Backhead thread types	90 ARDA, 3.5" Remet
Drill Bit Size Range	102mm – 114mm (4" – 4.5")
Hammer Weight (Less Bit)	40kg (88 lbs)
Maximum Drill Bit Weight	7.5kg (17 lbs)
Piston Weight	7.5kg (17 lbs)
Backhead Stand Off	0.75mm (0.03")
Recommended Minimum Air Package	425 L/s @ 24 bar (900 cfm @ 350 psi)



## Compatible drill bits - MR92

Description	Part Number	Diameter	Face Type	Quantity and size (inch)			Sample holes	Weight
				Outer	Face	Centre		
MR92 102mm HF Bit	509102H1	102mm (4")	Hard Formation	8 (1/2")	4 (1/2")	2 (1/2")	2	7.8kg (17.2 lbs)
MR92 105mm HF Bit	5092105H1	105mm (4.125")	Hard Formation	8 (1/2")	4 (1/2")	2 (1/2")	2	8kg (17.6 lbs)
MR92 108mm HF Bit	5092108H1	108mm (4.25")	Hard Formation	8 (1/2")	4 (1/2")	2 (1/2")	2	8.2kg (18.1 lbs)
MR92 114mm HF Bit	5092114H1	114mm (4.5")	Hard Formation	8 (9/16")	4 (9/16")	2 (1/2")	2	8.6kg (19 lbs)
MR92 117mm HF Bit	5092117H1	117mm (4.625")	Hard Formation	8 (9/16")	4 (9/16")	2 (1/2")	2	9kg (19.8 lbs)
MR92 146mm Collaring Bit	5092146C1	146mm (4.75")	Collaring	8 (5/8")	8 (1/2")	2 (1/2")	2	10.1kg (23 lbs)